



Building Quality Engineered Marine Products since 1946


Overhead Boat Lift



IB4500E Overhead Lift with Adjustable Slings

Overhead Lift Accessories

- ▶ I-Beam Cradles provide full length support of boat's hull and are ideal for choppy water or swift moving water conditions. (Wood bunks are not included.)
- ▶ Nylon Slings are adjustable and conform to the boat's hull. Sold in pairs of 2 in., 4 in. and 6 in. widths with hardware.
- ▶ Remote Control kits enable you to raise and lower your boat from up to 100 feet away.



I-Beam Cradles

RGC Advantage

The RGC IB4500 Overhead Lift raises your watercraft high above damaging rough water and debris.

Installation is easy using only basic hand tools and operation requires just the turn of a switch.

Adjustable legs allow the lift to adapt to deeper water and uneven lake bottoms. The frame is also adjustable allowing the slings or cradles to be positioned at the desired location on the boat's hull.

Customize your Overhead Lift with I-Beam Cradles, Nylon Slings, Remote Control, Catwalk Brackets or Skid Plates to best protect your boat.

Features & Benefits

- ▶ The IB4500 has a weight capacity of 4500 lbs.
- ▶ An exceptional lifting range make the Overhead Lift ideal for fluctuating water levels.
- ▶ Excellent lift for rough water and floating debris conditions.
- ▶ Durable galvanized steel frame requires minimal maintenance.
- ▶ Installation is easy with basic hand tools.
- ▶ Adjustable frame permits customizing to fit most boat dimensions.
- ▶ 18 in. adjustable legs accommodate a range of water depths.
- ▶ Power Drives are offered with or without an optional Remote Control feature.
- ▶ GFCI protection is standard on all power drives.
- ▶ Choose between Nylon slings and galvanized steel I-Beam Cradles to support your boat.
- ▶ Catwalk Brackets make your boat more accessible.
- ▶ A Wheel Kit and Skit Plates are offered to make moving Overhead Lifts easier.
- ▶ 5-year limited warranty on galvanized steel materials and workmanship for use in freshwater applications.

Specifications

Model	Weight Capacity	Maximum Beam	Overall Length	Overall Height	Maximum Width	Leg Adjustment	Weight
IB4500E	4500 lbs.	114 in.	132 in.-156 in.	148 in.-170 in.	162 in.	18 in.	940 lbs.

All measurements are approximate.

REIMANN & GEORGER CORPORATION

1.800.831.LIFT (5438)

www.rgcproducts.com

sales@rgcproducts.com

01.17 LE

Distributed by:

